

# MZ-3300-06

## Indoor - PoE – Integrated PIR - IP Camera



Industrial Video and Control

This color video camera with a wide angle vari-focal lens produces high quality video at a low cost. With a sophisticated 3-axis mechanical positioning system, the camera's industrial design offers easy, flexible installation on a ceiling or wall. The MZ-3300-06 supports dual codecs and is able to deliver both MPEG4 and M-JPEG video.



When the environment is short of sufficient light source, built-in infrared illuminators can be activated automatically or manually increase the camera's sensitivity in low light conditions.

The adjustable position mount and the 3.3 to 12 mm manual zoom lens can provide a horizontal field-of-view of up to 63.6 degrees.

The camera can accept one contact closure or TTL connect from auxiliary security or process-monitoring devices to initiate video recordings of intrusions or process upsets.

Installation is simplified since the camera only requires a powered Ethernet cable.

### Specifications

<b>Imager</b>	1/4" CMOS sensor	<b>Resolution</b>	352x240 & 704x480
<b>Shutter</b>	1/5 sec. to 1/15000 sec.	<b>Frame Rate</b>	30 FPS (352x240) 30 FPS (704x480)
<b>Exposure</b>	Auto	<b>Compression</b>	M-JPEG; MPEG4
<b>Min. Illumination</b>	0.56 Lux 0 Lux to 15 m w/ IR LEDs	<b>Protocols</b>	TCP/IP, HTTP, FTP, SMTP
<b>White Balance</b>	Auto	<b>Weight</b>	1.27 lbs
<b>Gain</b>	Auto	<b>Voltage Req.</b>	12 VDC, 110 VAC, PoE (IEEE 802.3af)
<b>Focus</b>	Manual	<b>Power Cons.</b>	11 W max.
<b>F-number</b>	1.4	<b>Operating Temperature</b>	0° to 50° C
<b>View Angle</b>	17.9° - 63.6°	<b>Dimensions</b>	5.63" D x 4.17" H
<b>Focal Length</b>	3.3 – 12 mm		
<b>Ethernet</b>	100Base-TX/10BaseT (RJ-45)		
<b>I/O Terminals</b>	One input, one output		