

# MZ-3313-NC1

## Indoor – Vandal-Resistant IP Camera

This vandal resistant, high-resolution color video camera with a vari-focal lens and auto-iris provides high quality video. The adjustable position mount and the 2.8 to 10 mm manual zoom lens can provide a horizontal field-of-view of up to 73 degrees.

The camera can accept one contact closure or TTL connect from auxiliary security or process-monitoring devices to initiate video recordings of intrusions or process upsets.

The enclosure is very rugged and vandal-resistant. The MZ-3313-NC1 offers a choice of professional networked fixed dome solutions for exposed indoor locations. Compact and discreet, it is ideal for the indoor surveillance of stores, schools, prisons, banks and other office buildings. The camera is ready for mounting and requires only a powered network connection.



### Specifications

<b>Imager</b>	1/4" CMOS sensor	<b>Resolution</b>	352x240 & 704x480
<b>Shutter</b>	1/4 to 1/15000 sec.	<b>Frame Rate</b>	30 FPS (352x240) 15 FPS (704x480)
<b>Exposure</b>	Auto	<b>Compression</b>	M-JPEG; MPEG4
<b>Min. Illumination</b>	1 Lux, f1.3	<b>Protocols</b>	TCP/IP, HTTP, FTP, SMTP
<b>White Balance</b>	Auto	<b>Weight</b>	2 lbs
<b>Iris</b>	Auto	<b>Power Input</b>	5 VDC (110VAC wall transformer supplied) or PoE
<b>Gain</b>	Auto	<b>Operating Temperature</b>	0° to 50° C
<b>Focus</b>	Manual	<b>Dimensions</b>	3.7" x 5.7" x 5.2"
<b>View Angle</b>	~20° - 73°		
<b>Focal Length</b>	2.8 - 10mm		
<b>Ethernet</b>	100Base-TX/10BaseT (RJ-45)		
<b>I/O Terminals</b>	One input, one output		