

ZO-3130-NC6

Outdoor – Zoom-Only – IP Camera

The ZO-3130-NC6 is a high quality, high-resolution color video camera with an 18x motor driven optical zoom and a 4x digital multiplier providing 72x total zoom, which can be controlled remotely through the IVC Relay Server. The ZO-3130-NC6 is a high performance low-light, day/night switching camera that automatically switches to black and white and removes an IR cut filter to increase sensitivity in low light conditions. The camera can accept contact closures or TTL connects from auxiliary security or process-monitoring devices to initiate automatic views and video recordings of intrusions or process upsets.



The camera is housed in a rugged enclosure with an automatic blower. The enclosure is dustproof, weather tight, and rated IP66.

The camera is ready for mounting and is powered over the Ethernet cable via PoE.

Specifications

Imager	1/4" Progressive Scan CCD	Ethernet	10/100BaseT Ethernet (RJ-45)
Shutter	1/60 to 1/10,000 Seconds	I/O Terminals	1 Inputs, 1 Output
Exposure	Auto	Resolution	704x480, 352x240
Min. Illumination	0.1 Lux (Color) 0.02 (B/W)	Compression	M-JPEG
White Balance	Auto	Frame Rate	30 FPS (at 352x240); 10 FPS (at 704x480)
Iris	Auto	Protocols	TCP/IP, HTTP, FTP, SMTP
Gain	Auto	Weight	10 lbs.
Focus	Auto and Manual	Power Requirement	PoE
Zoom Ratio	18x Optical, 4x Digital 72x Total	Power Consumption	10 W
View Angle	2.8° - 48°	Operating Temp	0° - 55° C
Focal Length	4.1 – 73.8 mm	Dimensions	5" H x 6.75" W x 21" L
F-number	1.4	Mount	Wall-mount Arm